# CS1644




## USB 2.0 DVI Dual View KVMP™ Switch

Supports two high resolution Dual Link displays

The CS1644 USB 2.0 DVI Dual View KVMP™ Switch charts a revolutionary new direction in KVM (Keyboard, Video, Mouse) switch functionality by combining a 4-port KVM switch with a 2-port USB 2.0 hub at the same time as providing dual-screen support for two DVI displays, making it ideal for graphic designers, banking and finance consultants, medical applications, and gamers. Moreover it carries advanced features, such as 120Hz 3D display support, gaming keyboard compatibility and port selection/switching using a mouse, aimed at giving you flexibility, convenience and enjoyment.

As a KVM switch, it allows users to access four computers with dual-screen support from a single USB keyboard, USB mouse, and dual-screen console. As a USB hub, it permits each computer to access any peripherals connected to the hub on a "one computer at a time" basis.





### **Features**

- · 4-port DVI Dual View KVMP switch with USB 2.0 support and 2.1 channel surround sound audio
- One dual-screen USB console controls four dual-screen computers and two additional USB devices
- 2-port USB 2.0 hub built in
- Fully compliant with the USB 2.0 specification
- Full bass response provides a rich experience for 2.1 channel surround sound systems
- · Independent switching of KVM, USB, and Audio focus
- DVI digital and analog monitor support fully compliant with the DVI specifications; also HDCP compliant
- Superior video quality: 1920 x 1200 @ 60Hz (Single Link); 2560 x 1600 @ 60Hz (Dual Link): Works with cutting edge 120Hz LCD monitors and active shutter glasses to create a 3D environment with maximum resolution of up to 1920 x 1080 for your ideal workspace and entertainment
- · Supports widescreen resolutions
- · Computer selection via front panel pushbuttons and hotkeys
- Multiplatform support Windows, Linux, Mac, Sun
- Console mouse port emulation / bypass feature supports most mouse drivers and multifunction mice
- Video DynaSync™ stores the console monitors EDID (Extended Display Identification Data) to optimize display
- · Complete keyboard emulation for error-free booting
- Sun/Mac keyboard support and emulation
- · Auto Scan Mode for monitoring all computers
- · Firmware upgradable

## Specifications -----

Function			CS1644
Computer Connections			4
Port Selection			Front Panel Pushbuttons; Hotkeys
Connectors	Console Ports	Keyboard	1 x USB Type A Female (White, rear panel)
		Video	2 x DVI-I Female (White)
		Mouse	1 x USB Type A Female (White, rear panel)
		Speakers	1 x Mini Stereo Jack Female (Green)
		Microphone	1 x Mini Stereo Jack Female (Pink)
	KVM Ports	Keyboard/ Mouse	4 x USB Type B Female (white)
		Video	8 x DVI-I Female (white)
		Speakers	4 x Mini Stereo Jack Female (Green)
		Microphone	4 x Mini Stereo Jack Female (Pink)
	F/W Upgrade		1 x 4-conductor 3.5 mm Jack
	Power		1 x DC Jack
	USB 2.0 Hub		2 x USB Type A Female (Black; 1 x front panel; 1 x rear panel)
Switches	Selected		5 x Pushbutton
LEDs	Mode		3 (1 Orange, 2 Green)
	KVM		4 (Orange)
	Audio		4 (Green)
	USB		4 (Green)
Emulation	KB / Mouse		USB
Video			DVI Dual Link: 2560 x 1600 DVI Single Link: 1920 x 1200
Scan Interval			1-99 secs. (5 secs. default)
Power Consumption			DC 5.3 V, 12.19 W
Environment	Operating Temp.		0-50°C
	Storage Temp.		-20-60°C
	Humidity		0-80% RH, Non-condensing
Dhariad	Housing		Metal
Physical Properties	Weight		2.32 kg
Toperties	Dimensions (L x W x H)		43.24 x 15.41 x 4.40 cm

