



USER MANUAL

HDMI SWITCH 5x1 (4K@60Hz)

Enjoy the vivid world!

INTRODUCTION

The 5x1 HDMI switch allows 5 HDMI ports to be switched to a single display terminal via remote control or buttons on unit. The switcher can be placed at the end of a long HDMI cable to regenerate the HDMI signal. The HDMI switcher can support all hd formats including 720p, 1080i, 1080p, 4K/30Hz, 4K/60Hz .




Features:

- * Support 6x3Gbps data rate for trnds clock up to 600MHz.
- * Support 3D.
- * Supports highest video resolution 4K/60Hz.
- * Support HDR.
- * Support automatic switching of HDMI input ports (for 5 ports, the last one has priority).
- * Support 24/30/36 bit deep color .
- * Support AWG26 HDMI standard cable, Input up to 8metres ,output up to 8metres (4K/30Hz resolution and below).
- * Support 2.0 HDMI standard cable, input up to 3 meters, output up to 5 meters (4K/60Hz resolution).
- * Supports single high definition display for multiple sources, such as DVD Players, PS4 and HD players, Set Top Boxes.


Specifications:

HDMI resolution	4K/60Hz
Support video format	3D
Support video color format	24/30/36 bit deep color
Support audio format.....	DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD
Max bandwidth.....	600MHz
Max baud rate.....	6Gbps
Input cable distance.....	≤8m AWG26 HDMI standard cable(4K/30HZ); ≤3m 2.0 HDMI standard cable(4K/60HZ);
Output cable distance.....	≤8m AWG26 HDMI standard cable(4K/30HZ); ≤5m 2.0 HDMI standard cable(4K/60HZ);
Max working current.....	400mA
Operating Temperature range.....	(-10 to +55 ℃)
Dimension (L x W x H).....	122x56x15 (mm)
Weight.....	95g

Operating and Connecting



Application diagrams



- 1: Connect five HDMI cables from HDMI source device into HDMI switch input.
- 2: Connect one HDMI cable from HDMI source device into HDMI switch output.
- 3: Through a MICRO USB cable to connect the power to the switch .

The Package includes:

- | | |
|----------------------|-------|
| 1. HDMI Switch | 1 PCS |
| 2. IR Remote Control | 1 PCS |
| 3. MICRO USB cable | 1 PCS |
| 4. User Manual | 1 PCS |