


# USB HDMI Dual View HDBaseT™ 2.0 KVM Extender

## CE824

ATEN CE824 adopts HDBaseT 2.0 technology to transmit uncompressed HDMI video, stereo audio, USB, and RS-232 signals while supporting up to 4096 x 2160 @ 30Hz (4:4:4) on a single display / 1080p on dual displays across 100 m over a single Cat 6 / 6A cable (ATEN 2L-29330 recommended), allowing access to a distant computer for KVM control from the remote console. With Long Reach Mode enabled, the CE824 can extend 1080p HDMI source along with other signals up to 150 m.\* The ease of cabling installation plus the rack mount compatibility assure a more efficient system setup. The CE824 serves as an ideal solution for applications that require high-quality multi-signal extension and KVM control across long distances – such as control centers, banking and finance sectors, industrial warehouses, and extended workstations.

**Note:** 1080p @ 150 m can only be achieved via single display installation.



CE824L



CE824R



Front View



CE824L



CE824R

Rear View



CE824L




CE824R

## Features

- Allows HDMI dual view access to a distant computer for KVM control from remote console
- Transmits uncompressed HDMI video / stereo audio / USB / RS-232 signals via one single Cat 6 / 6A / ATEN 2L-29330 cable over long distances:
  - Standard mode supports single view at up to 4K or dual-view up to 1080p over 100 m
  - Long Reach mode supports single view at up to 1080p or dual-view up to 720p over 150 m\*
- 4 x USB 2.0 Type-A ports on the remote unit for connection to multiple USB peripherals
- Supports 2-channel stereo audio
- EDID buffer for smooth power-up and the highest quality display
- PC wakeup function enabled via a pushbutton through RS-232
- HDCP compatible
- Built-in 8KV / 15KV ESD protection (Contact voltage 8KV; Air voltage 15KV)
- DC Jack with screw-lock ensures stable and secure connection
- Rack mountable

**Note:** 1080p @ 150 m can only be achieved via single display installation.



## Specifications

	CE824L	CE824R
<b>Connectors</b>		
KVM Ports	2 x HDMI Female (Black) 1 x USB Type-B Female (White) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink)	N/A
Console Ports	N/A	2 x HDMI Female (Black) 4 x USB Type-A Female (White) 1 x Mini Stereo Jack Female (Green) 1 x Mini Stereo Jack Female (Pink)
RS-232	1 x DB-9 Female (Black)	1 x DB-9 Male (Black)
Power	1 x DC Jack (Black) with locking	1 x DC Jack (Black) with locking
Unit To Unit	1 x RJ-45 Female (Black)	1 x RJ-45 Female (Black)
<b>LEDs</b>		
Power	1 (Green)	1 (Green)
Link	1 (Orange)	1 (Orange)
Video Output	N/A	2 (Orange)
<b>Switches</b>		
Long Reach Mode Switch	1 x Slide Switch	1 x Slide Switch
Firmware Upgrade	1 x Slide Switch	1 x Slide Switch
<b>Pushbuttons</b>		
Wakeup Button	N/A	1 x Pushbutton
Video	Single view: Up to 4K @ 100 m (Cat 6/6A/ATEN 2L-29330 Cat 6A) 1080p @ 150 m (Cat 6/6A/ATEN 2L-29330 Cat 6A) with Long Reach Mode enabled Dual-view: Up to 1080p @ 100 m (Cat 6/6A/ATEN 2L-29330 Cat 6A)	
	*4K supported: 4096 x 2160 @ 60Hz (4:2:0) ; 4096 x 2160 / 3840 x 2160 @ 30 Hz (4:4:4)	
Power Consumption	DC12V:5.98W	DC12V:10.32W
<b>Environmental</b>		
Operating Temperature	0 – 40°C	
Storage Temperature	-20 – 60°C	
Humidity	0 – 80% RH, Non-condensing	
<b>Physical Properties</b>		
Housing	Metal	
Weight	0.79 kg	0.82 kg
Dimensions (L x W x H)	17.42 x 15.59 x 2.88 cm	
17.42 x 15.59 x 2.88 cm		

### ATEN International Co., Ltd.

3 F, No. 125, Sec. 2, Datong Rd., Xizhi Dist., New Taipei City 221, Taiwan  
 Phone: 886-2-8692-6789 Fax: 886-2-8692-6767  
[www.aten.com](http://www.aten.com) E-mail: [marketing@aten.com](mailto:marketing@aten.com)

Product information is subject to change without prior notice.

Released: 11/2025 V1.0

© Copyright 2025 ATEN® International Co., Ltd.  
 ATEN and the ATEN logo are registered trademarks of ATEN International Co., Ltd.  
 All rights reserved. All other trademarks are the property of their respective owners.  
 The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the  
 HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

